

## **Declaration of Performance (DoP)**

# CE

According to Construction Products Regulation (EU) No 305/2011 Declaration number: **PFD-CPR-0101** 

- 1. Unique identification code of the product-type: 6000/SSR/VAD
- 2. Identification of the construction product as required under Article 11(4) of the CPR:

#### Analogue addressable type A/B sounder (colour red) complete with visual alarm and isolator

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Fire detection and fire alarm systems for use in and around buildings

4. Name and address of the manufacturer as required under Article 11(5):

Protec Fire Detection plc, Protec House, Churchill Way, Nelson, Lancashire, BB9 6RT, ENGLAND Telephone number: + 44 (0)1282 717171 Fax number: +44 (0)1282 717273 Web: www.protec.co.uk

- 5. Name and contact address of authorized representative whose mandate covers the tasks specified in Article 12(2) **Not applicable**
- 6. System of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Notified Body: Intertek Testing and Certification Ltd, Cleeve Road, Leatherhead, Surrey, KT22 7SB. Telephone: +44(0)1372 370900, Fax: +44(0)1372 370977, E-mail:cpd.uk@intertek.com Notified Body number : 0359 performed the type testing and initial inspection of the manufacturing plant and of factory production control with continuous surveillance, assessment and evaluation of factory production control under system 1 and issued the following certificate of constancy of performance: 0359-CPR-00409

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: (Not applicable, see item 7)

## **Declaration of Performance (DoP)**

#### 9. Declared performance:

All requirements including the Essential Characteristics and the corresponding performances for the intended use or uses indicated in (3), above have been determined as described in the harmonised European standard(s) (hEN) mentioned in the following table.

Essential characteristics	Performance	EN) mentioned in the following table. Harmonised tech	nical specification (hEN)
		4.2, 4.3. 5.2, 5.3, C.3.1,	
Performance under fire condition	Pass	C.3.2,C.5.1,C.5.2,C.5.3	EN 54-3:2001 + A1: 2003+A2:2006
Operational reliability	Pass	4.4, 4.5, 4.6, 5.4, C4	EN 54-3:2001 + A1: 2003+A2:2006
Durability of operational reliability,	Pass	5.5,5.6, 5.7, 5.8, 5.9	EN 54-3:2001 + A1: 2003+A2:2006
temperature resistance	1 400	0.0,0.0, 0.7, 0.0, 0.0	
Durability of operational reliability, humidity resistance	Pass	5.8, 5.9,5.10	EN 54-3:2001 + A1: 2003+A2:2006
Durability of operational reliability, corrosion resistance	Pass	5.11	EN 54-3:2001 + A1: 2003+A2:2006
Durability of operational reliability, shock and vibration resistance	Pass	5.12 to 5.15	EN 54-3:2001 + A1: 2003+A2:2006
Durability of operational reliability, electrical stability	Pass	5.16	EN 54-3:2001 + A1: 2003+A2:2006
Durability of operational reliability, resistance to ingress	Pass	5.17	EN 54-3:2001 + A1: 2003+A2:2006
Essential characteristics	Performance	Harmonised tech	nical specification (hEN)
Performance under fire conditions	Pass	5.2	EN54-17:2005+AC:2007
Operational reliability	Pass	4	EN54-17:2005+AC:2007
Durability of operational reliability, temperature resistance	Pass	5.4, 5.5	EN54-17:2005+AC:2007
Durability of operational reliability, vibration resistance	Pass	5.9 to 5.12	EN54-17:2005+AC:2007
Durability of operational reliability, humidity resistance	Pass	5.6, 5.7	EN54-17:2005+AC:2007
Durability of operational reliability, corrosion resistance	Pass	5.8	EN54-17:2005+AC:2007
Durability of operational reliability, electrical stability	Pass	5.3, 5.13	EN54-17:2005+AC:2007
Essential characteristics	Performance	Harmonised tech	nical specification (hEN)
Operational reliability: Duration of operation Provision for external conductors Flammability of materials Enclosure protection Access Manufacturers adjustments On-site adjustment of behaviour Requirements for software controlled devices	Pass	4.2.1 4.2.2. 4.2.3 4.2.4 4.2.5 4.2.6 4.2.7 4.2.8	EN 54-23:2010
Performance parameters under fire condition: Coverage volume Variation of light output Minimum and maximum light intensity Light colour Light temporal pattern and frequency of flashing Marking and data Synchronisation (option with requirements)	Pass	4.3.1 4.3.2 4.3.3 4.3.4 4.3.5 4.3.6 4.3.7	EN 54-23:2010
Durability: Temperature resistance Dry heat (operational) Dry heat (endurance) Cold (operational) Humidity resistance Damp heat, cyclic (operations) Damp heat, steady state (endurance) Damp heat, cyclic(endurance) Shock and vibration resistance Shock (operational)	Pass	4.4.1.1 4.4.1.2 4.4.1.3 4.4.2.1 4.4.2.2 4.4.2.3 4.4.3.1	EN 54-23:2010

Impact (operational)	4.4.3.2	
Vibration (operational)	4.4.3.3	
Vibration (endurance)	4.4.3.4.	
Corrosion resistance		
SO2 corrosion (endurance)	4.4.4	
Electrical stability		
EMC, immunity (operational)	4.4.5	

10. The performance of the product indentified in (1) and (2), is in conformity with the declared performance in (9). This declaration of performance is issued under the sole responsibility of the manufacturer indentified in (4)

### **Declaration of Conformity**

This Declaration of Performance also serves as a **CE Declaration of Conformity** for the product regarding the following additional European Directives and relevant standards:

 Electromagnetic Compatibility Regulation 2006 SI No.2006/3148. (which implements the Council Directive 2004/108/EC "the EMC Directive")

European Harmonised standards (hEN):

EN 50130-4:2011 (immunity tests in conjunction with external type testing) EN 61000-4:2007/A1:2011 (emission tests, self-declared through arranged tests)

Electrical Equipment (Safety) Regulation 1994 SI 3260 (which implements Council Directive 2006/95/EC the "Low Voltage Directive"):

European Harmonised standard (hEN): EN 60950-1:2006/A11:2009

- The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 No. 3032 (which implements Council Directive 2011/65/EU the "RoHS2 Directive"):
- IP 65: Degrees of protection against foreign objects and against moisture.

BS EN 60529:1992+A2:2013 Degrees of protection provided by enclosures (IP code)

I hereby declare that the equipment named above has been designed to comply with the relevant sections of the above referenced specifications. The named product complies with all applicable Essential Requirements of the Directives.

Signed for and on behalf of the manufacturer:

Khellafforiz

Name: Dr Fariz Khellaf Position: Technical Director

Protec Fire Detection PLC, Lomeshaye Industrial Estate, Churchill Way, Nelson. Lancashire. England, BB9 6RT

July 20th 2015

