

## DUOX PLUS AUDIO VEO GUARD UNIT



**Reference:** 9423

### FUNCTIONS

- 4 mechanical buttons with pleasant touch for basic functions
- Headset with magnet for easy hanging.
- Audio Full-Duplex.
- Privacy in conversation.
- Red status LED.
- Capacitive and pa...

## DESCRIPTION

### FUNCTIONS

- 4 mechanical buttons with pleasant touch for basic functions
  - Headset with magnet for easy hanging.
  - Audio Full-Duplex.
  - Privacy in conversation.
  - Red status LED.
  - Capacitive and panoramic touch screen (size 4.3" and format 16:9). Resolution 480 x 272 pixels.
  - Make calls to homes, outdoor panels or concierge.
  - The concierge can transfer the call to a flat or to another concierge.
  - Reception of calls from dwellings, outdoor panels or other guard units.
  - Communication between two dwellings through the caretaker.
  - Establishing a connection with the outdoor panels to open the door. List of selectable outdoor panels of the installation.
  - User interface in 28 languages. - 10 selectable ring tones.
  - Call duration 30 s.
  - 8 volume levels. Volume level can be selected for calls, conversation and touch screen sound.
  - No-message mode (ring tone mute).
  - Deactivation of the microphone during the conversation (Mute).
  - Registration of missed calls. Maximum of 50 calls of each type (houses, outdoor panels, guard units).
  - Screen brightness control (8 levels).
  - Selection between 3 operation modes: Day, Mixed and Night. - Day: receives calls from access points and homes. The calls from the panel to the home are always sent to the guard unit. - Mixed: calls from the panel are received in the home and can also be configured to be diverted to the guard unit after 15 seconds. - Night: only allows calls to homes. No call is received.
  - Some configuration menus have restricted access by pin code. Different code for installer and janitor.
  - Possibility of programming terminals (monitors and telephones) from the central guard unit.
  - Winter/Summer time configuration with 3 options: Europe, America or manual. - Available in 12h or 24h format. - 3 different date formats: DD/MM/YYYY, MM/DD/YYYY, YYYY/MM/DD.
  - Agenda for up to 10,000 home users, 70 outdoor panels and 30 concierge panels. It is possible to search by name.
  - Touch screen lock function for cleaning.
  - Possibility of connecting a call extension (ref. 2040) or a light and bell activator (ref. 2438) through terminals "-" and "A".
  - Tabletop support included, made of high quality stainless steel (AISI316L) and resistant to corrosion.
- BASIC PUSHBUTTON OPERATORS** - MENU: access to the main menu on the screen, easy to use for the operation and configuration of parameters. - Door opening. - To make calls to homes, panels and caretakers. - See missed calls register.
- LEDs** - Red LED off when the screen is activated. - Red LED on when the screen is off. - Red LED flashes when there are missed



calls pending to be checked.

## TECHNICAL SPECIFICATIONS

### MECHANICAL FEATURES

Color: Black Material: ABS with UV protection. DIMENSIONS 200 x 200 x 46 mm. Desktop support (316L quality stainless steel support). Stand inclination: 60°

### TECHNICAL FEATURES

PSU: - 18-24 Vdc Estimated maximum consumption: - Standby (display off): 75 mA. - Conversation with audio at maximum: 255 mA. - Call with volume at maximum: 270 mA. Operating temperature: 5°C, +40°C] / [41°F, 104°F]. Operating humidity: 0%, 90%] Capacitive touch screen: - Size 4.3", Format 16:9 - Resolution: 480 x 272 Audio features: - Digital DUOX PLUS audio. - Speakers: 1 x 1W. Technology: digital DUOX PLUS system (2 non-polarized wires) No. of guard units per installation: 10 in General Entrance / 10 per Block

### TECHNICAL SPECIFICATIONS

CONNECTIONS B, B: DUOX PLUS bus. +A: connection for external devices (call extension ref. 2040, light and bell activator ref. 2438). -: negative (electrical reference). +12V: 12Vdc output (not used in this product). P: connection not used in this product. A, B: RS485 bus (not used in this product). Terminal block with RJ45 connector to facilitate connection/disconnection with the DUOX PLUS bus.

**Weight:** 2,3639 kg

**Size of product when packed:** 29x26x24,5 cm

**EAN 13:** 8424299094236