

## AXIS T8133 30 W Midspan

Widely used for PoE-based devices

Power over Ethernet (PoE) offers an easy, fast and cost-effective solution for powering network products. A midspan injects power and data to the network device with built-in PoE support. No need to replace existing Ethernet switches and cabling infrastructure. AXIS T8133 30 W Midspan is a 1-port midspan, delivers 30 W and is IEEE 802.3at compliant, which ensures compatibility with most of Axis network products with built-in PoE.

- > **IEEE 802.3at**
- > **100 to 240 V AC**
- > **Plug-and-play**



# AXIS T8133 30 W Midspan

Midspans	
<b>Function</b>	Data and power are fed to a network video product through an Ethernet cable Use together with a PoE splitter for a network video product without built-in PoE support
<b>Data rate</b>	10/100/1000 Mbps
<b>Installation and management</b>	Power Selector: 15 W or 30 W Automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display Should be used with a non-PoE network switch. If a PoE switch is used, turn off the PoE on the port in use
Data & power	
<b>Power</b>	Power over Ethernet Plus (PoE+) IEEE 802.3at Type 2 Class 4
<b>Input power</b>	AC Input Voltage: 100 to 240 V AC AC Frequency: 50-60 Hz
<b>Max. output power</b>	55 V DC (max. 30 W)
<b>Connectors</b>	Shielded RJ45, EIA 568A and 568B Power connector C13
<b>Network cables</b>	Shielded category 5 (or higher)
<b>Wiring</b>	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over spare pairs 4/5 (+) and 7/8 (-)

General	
<b>Display and indicators</b>	Port interfaces are located on the front panel Port LED: Power indicator and Data connectivity
<b>Mounting</b>	Wall, shelf or DIN rail <sup>a</sup>
<b>Operating conditions</b>	-20 °C to 40 °C (-4 °F to 104 °F) At 22.5 W: -20 °C to 55 °C (-4 °F to 131 °F) Humidity 10–90% RH (non-condensing)
<b>Approvals</b>	RoHS, REACH, WEEE, CE, EN 55022 Class B, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1, GS, CB, CCC
<b>Dimensions</b>	33 x 53 x 140 mm (1.3 x 2.1 x 5.5 in)
<b>Weight</b>	200 g (0.4 lb)
<b>Optional accessories</b>	AXIS T91A03 DIN Rail Clip Mains Cable Angle C13-Open 0.5 m
<b>Warranty</b>	Axis 3-years warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

a. Sold as optional accessory

Environmental responsibility:  
[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)