

# AXIS T8134 60 W Midspan

For high power devices

Power over Ethernet (PoE) offers an easy, fast and cost-effective solution for powering network products. A midspan injects power and data to the network device with built-in PoE support. No need to replace existing Ethernet switches and cabling infrastructure. AXIS T8134 60 W Midspan provides 60 W (two times IEEE 802.3at) that is required when operating e.g. AXIS Q60-E Network Cameras in temperatures below -20 °C (-4 °F).

- > IEEE 802.3at
- > 100 to 240 V AC
- > Support for Axis PTZ domes
- > Plug-and-play



Data



PoE



# AXIS T8134 60 W Midspan

Midspans	
<b>Function</b>	Data and power are fed to a network video product through an Ethernet cable Use together with a PoE splitter for a network video product without built-in PoE support
<b>Data rate</b>	10/100/1000 Mbps
<b>Installation and management</b>	Power Selector: 15 W or 30 W Automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display
Data & power	
<b>Input power</b>	AC Input Voltage: 100 to 240 V AC AC Frequency: 50-60 Hz
<b>Max. output power</b>	55 V DC (max. 60 W)
<b>Connectors</b>	Shielded RJ45, EIA 568A and 568B Power connector C13
<b>Network cables</b>	Shielded category 5 (or higher)
<b>Wiring</b>	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over pairs 1/2 (-), 3/6 (+), 4/5 (+) and 7/8 (-)

General	
<b>Display and indicators</b>	Port interfaces are located on the front panel Port LED: Power indicator and Data connectivity
<b>Mounting</b>	Wall, shelf or DIN rail <sup>a</sup>
<b>Operating conditions</b>	-10 °C to 45 °C (14 °F to 113 °F) <b>At 30 W:</b> -10 °C to 55 °C (14 °F to 131 °F) Humidity max. 90% RH (non-condensing)
<b>Approvals</b>	RoHS, REACH, CB, WEEE, CE, EN 55022 Class B, EN 61000 3-2, EN 61000 3-3, EN 55024, FCC Part 15 Subpart B Class B, VCCI Class B, RCM AS/NZS CISPR22 Class B, KC, KCC KN22 Class B, KN24, CCC, S-Mark, IEC/EN/UL 60950-1, GS Mark per EN 60950-1
<b>Dimensions</b>	38 x 62 x 151 mm (1.5 x 2.4 x 5.9 in)
<b>Weight</b>	320 g (0.7 lb)
<b>Optional accessories</b>	AXIS Midspan DIN Clip A Mains Cable Angle C13-Open 0.5 m
<b>Warranty</b>	Axis 3-years warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

a. Sold as optional accessory

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)