

GV-IO Box 8 Ports



The GV-IO Box 8 provides 8 inputs and 8 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

Specifications		
OS Supported	32-bit	Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2008
	64-bit	Windows 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 / Server 2012 R2
Compatible S/W	GV-System version 8.2 or above	
Input	Input	8
	Input Signal	Dry Contact Wet Contact, 9-30V AC / DC
Communication	Relay Output	8
	Relay Status	Normal open
	Relay Capacitance	USB Connection
RS-485 Connection		125 / 250V AC, 3A 30V DC, 3A
Ethernet	RJ-45, 10/100 Mbps (Optional)	
DC IN	DC 12V, 1A	
Address	0-9, A-F	
Terminal Resistance	120 ohm	
Environmental Conditions	0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)	
Dimensions (W x H x D)	135 x 28 x 145 (mm) / 5.31x 1.10 x 5.70 (in)	
Installation Guide	GV-IO Box 8	

Note: All specifications are subject to change without notice.