

GV-IO Box 16 Ports



The GV-IO Box 16 provides 16 inputs and 16 relay outputs. It supports both DC and AC output voltages, and provides a USB port for PC connection.

Specifications			
OS Supported	32-bit		Windows XP / Vista / 7 / 8 / 8.1 / 10 / Server 2008
	64-bit		Windows 7 / 8 / 8.1 / 10 / Server 2008 R2 / Server 2012 / Server 2012 R2
Compatible S/W			GV-System version 8.2 or above
Input	Input		16
	Input Signal		Dry Contact
			Wet Contact, 9-30V AC / DC
Communication	Relay Output		16
	Relay Status		Normal open
	Relay Capacitance	USB Connection	30V DC, 3A
		RS-485 Connection	125 / 250V AC, 3A 30V DC, 3A
Ethernet			RJ-45, 10/100 Mbps (Optional)
DC IN			DC 12V, 1A
Address			0-9, A-F
Terminal Resistance			120 ohm
Environmental Conditions			0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)
Dimensions (W x H x D)			180 x 27 x 183 (mm) / 7.09 x 1.06 x 7.2 (in)
Installation Guide			GV-IO Box 16

Note: All specifications are subject to change without notice.