

	Item	Description
Power	Power Supply	Power Adapter DC12V1A
	Voltage Range	DC 12V-24V
	Consumption	<5W
Network Connector	Network Port	1~4: 10/100Mbps Ethernet port UPLINK Port: 10/100Mbps Ethernet port SFP: 100Mbps Optical SFP Module interface
	Transmission Distance	UPLINK port: 0~150m SFP: Depend on the optical module
	Transmission Medium	Cat5/5e/6 Standard Network Cable
Network Switch	Network Standard	IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX; IEEE802.3u 100BASE-FX; IEEE802.3 X
	Switch Way	Store and forward
	Package Data Cache	512K
	MAC address list	2K
LED Status Indicators	Power	1 (red)
	Optical Port	1 SFP port indicator (green)
	Uplink Network Port	1 network working status indicator, green light on the RJ 45 socket
	Network Port	4 network working status indicators, green light on the RJ 45 socket
Protection	Communication Port	4KV per: IEC61000-4-5
	ESD	1a contact discharge, level 3 1b air discharge, level 3 Per: IEC61000-4-2
Environmental	Working temperature	-40°C-75°C
	Storage temperature	-40°C-85°C
	Humidity (non-condensing)	0-95%
Mechanical	Dimension (LxWxH)	159mmx110mmx46.5mm
	Material	Aluminum
	Color	Black
	Weight	533g
Stability	MTBF	>30000h