

NGC-7201F

| Model | 1.3 Megapixel Water-proof Network Dome Camera | |
|-----------|---|---|
| Camera | Image Sensor | 1/3 " CMOS |
| | Image Size | 1280 × 960 |
| | Electronic Shutter | 1/25s~1/100000s |
| | Auto Iris | Fixed Iris |
| | Min. Illumination | 0 Lux (IR ON) |
| | Lens | 3.6mm (2.8mm, 6mm optional) |
| | Day-Night Switch | ICR auto switch |
| | WDR | Digital WDR |
| | DNR | 3D noise reduction |
| Image | Video Compression | H.264/MJPEG |
| | H.264 Compression | Baseline Profile/Main Profile |
| | Encode Mode | VBR/CBR |
| | Image Quality | Five levels VBR; Freely adjustable under CBR |
| | Bitrate | 64Kbps~4Mbps |
| | Resolution | 960P(1280 × 960), 720P(1280 × 720), D1, CIF, 480 × 240 |
| | Multi-streams | 1280 × 960 (1~30fps) /1280 × 720 (1~30fps) 1280 × 720 (1~10fps) /D1 (1~30fps) /CIF (1~30fps) CIF (1~30fps) /480 × 240 (1~30fps) |
| | Image Settings | Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc., adjustable through client software or web browser |
| | ROI | Support 8 ROI areas |
| Interface | Network | RJ45 |
| Function | Remote Monitoring | IE browsing, CMS remote control |
| | Online Connection | Support simultaneous monitoring for up to 4 users; Support multi-stream real time transmission |
| | Network Protocol | TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP |
| | Interface Protocol | ONVIF, GB-T/28181-2011 |
| | Storage | Network remote storage |
| | Smart Alarm | Motion Alarm |
| | PoE Power Supply | Support |
| | IR Distance | No (10-20 m optional) |
| | Vandal-proof | IK10 |
| | Water-proof | IP66 |
| Others | Power Supply | DC12V/PoE |
| | Power Consumption | < 2.5W (ICROFF); < 4.5W(ICR ON) |
| | Working Environment | -20℃~50℃, 10%~90% humidity |
| | Dimension | Φ 116mm × 91mm |
| | Weight (Net) | 594g |