


NGC-7322FS


2 MP Network IR Water-proof Bullet Camera



2MP (1920 x 1080) full real time
coding Max. resolution:1920 x 1080
ICR auto switch, true day / night
20 ~ 30m IR night view distance
3D DNR, digital WDR, ROI
coding PoE power supply
Support smart phone, iPad, remote
monitoring IP66 ingress protection
Support dual streams




2 MP Network IR Water-proof Bullet Camera



Features

- 2MP (1920 x 1080) full real time coding
- Max. resolution:1920 x1080
- ICR auto switch, true day / night
- 20 ~ 30m IR night view distance
- 3D DNR, digital WDR, ROI coding
- PoE power supply
- Support smart phone, iPad, remote monitoring
- IP66 ingress protection
- Support dual streams

Dimensions



Available Accessories



NAV-DJB



NAV-DJB + NAV-SAS



NAV-DJB + NAV-SAC

Specifications

Model	NGC-7322FS
Specifications	
Camera	
Image Sensor	1 / 2.7 "CMOS
Image Size	1920 x1080
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.007lux @F1.2, AGC ON; 0 lux with IR
Lens	2.8 mm @ F1.85, horizontal field of view : 102° 3.6 mm @ F2.0, horizontal field of view : 97° 6 mm @ F1.6, horizontal field of view: 54.5° 2.8 ~ 12 mm @ F1.4, horizontal field of view : 99.4° ~ 40.6°
Lens Mount	M12 or Φ14 optional
Day & Night	ICR
Wide Dynamic Range	Digital WDR
Digital NR	3D DNR
Angle Adjustment	Any angle
Image	
Video Compression	H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile@Level4.1 High Tier
Resolution	1080P (1920 x 1080), 720P (1280 x 720), D1, CIF, 480 x 240
Main Stream	60Hz : 1080P (1 ~ 30fps) / 720P (1 ~ 30fps) 50Hz : 1080P (1 ~ 25fps) / 720P (1 ~ 25fps)
Bit Rate	256Kbps ~ 5Mbps
Encode Mode	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
ROI	Yes
Interfaces	
Network	RJ45
Functions	
Remote Monitoring	Web browsing,CMS remote control
Online Connection	Support simultaneous monitoring for up to 4 users ; Support multi-stream real time transmission
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, DDNS, SMTP,FTP
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion alarm
PoE	Yes
IR Distance	20 ~ 30 m
Water-proof	IP66
Others	
Power Supply	DC 12V / PoE
Power Consumption	< 6W
Operating Environment	- 30°C ~ 60°C, ≤95% humidity
Dimensions (mm)	Φ87 × 219
Weight (net)	560g
Installation	Wall mounting, ceiling mounting