



**SPECIFICATIONS**

Model NO.	NVL-N4.4P
<b>System</b>	
Main Processor	ARM Cortex A9 Processor(HI3520D)
Operating System	Embedded LINUX
<b>Video</b>	
Input	4CH (1920x1080, 1280x960, 1280x720, etc)
Output	1 VGA, 1 HDMI
<b>Audio</b>	
Input	/
Output	/
Audio Bit Rate	64kbps
Audio Compression standard	G.711
<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	4 Channel, MD Zones: 396 (22 × 18)
Trigger Events	Recording, Email, FTP, Snapshot, Buzzer and Screen Tips
<b>Display</b>	
HDMI1	resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
HDMI2	\
VGA	resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
Display Split	4 Channel / 1Channel
Digital Zoom	YES
OSD	Camera Title, Time, Video Loss, Recording, Motion Detection
<b>Recording</b>	
Video Compression	H.264
Resolution	1080P(1920x1080),960P(1280x960),720P(1280x720),D1 (720x576/720x480)
Record Rate	PAL : 1080P@4x25fp, 960P@4x25fp,720P@4x25fp, D1@4x25fp NTSC: 1080P@4x30fp, 960P@4x30fp, 720P@4x30fp, D1@4x30fp
Record Mode	Manual\Timer\Motion Detection
<b>Playback &amp; Backup</b>	
Local Sync Playback	1CH 1080P@30fps, 1CH 960P@30fps, 1CH 720P@30fps
Decode Capability	1CH 1080P@30fps
Remote Sync Playback	YES
Search Mode	ALL, Channel, Time, Date, Motion Detection

Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
Backup Mode	USB Device/Network
<b>Network</b>	
Interface	1 RJ45 10M/100M Adaptive Ethernet Interface
Incoming Bandwidth	24MB
Network Functions	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Search, P2P
Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android PAD
POE	/
WIFI	/
<b>Storage</b>	
Interface Type	1 SATA Interface
Capacity	Up to 6TB capacity
eSATA	/
<b>General</b>	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces
RS485	/
Power Supply	DC12V/2A
Working Environment	-10~55°C/10~90%
Dimension(W×D×H)	260*215*43(mm)
Weight	2.0KG (without HDD)