

SANDOR SMA HY	PARVIS SMA HY	SANDOR SOLAR SMA	PARVIS SOLAR SMA
400 m	400 m	200 m	200 m
100 m	100 m	50 m	50 m
SMA	SMA	SMA	SMA
optical with 4 channels	optical with 4 channels	optical with 4 channels	optical with 4 channels
Yes with 35mm lenes (And)	Yes with 35mm lenes (And)	Yes with 35mm lenes (And)	Yes with 35mm lenes (And)
Pulsed 950nM beams	Pulsed 950nM beams	Pulsed 950nM beams	Pulsed 950nM beams
	2-3TX 2-3RX		2-3TX 2-3RX
2-3-4-5-6TX e 2-3-4-5-6RX	2-3TX 2-3RX	2-3-4-5-6TX 2-3-4-5-6RX	2-3TX 2-3RX
Parallel	Parallel	Parallel	Parallel
OR - AND RANDOM	OR - AND RANDOM	OR - AND RANDOM	OR - AND RANDOM
yes	yes	yes	yes
yes	yes	yes	yes
rechargeable Battery 3,6V 3,2Ah	rechargeable Battery 3,6V 3,2Ah	rechargeable Battery 3,6V 3,2Ah	rechargeable Batterie 3,6V 3,2Ah
3 months (without mains power)	3 months (without mains power)	3 months (without mains power)	3 months (without mains power)
Free contact relay (NC NO) on RX	Free contact relay (NC NO) on RX	Free contact relay (NC NO) on RX	Free contact relay (NC NO) on RX
Free contact relay (NC NO) on RX (also for TX tamper)	Free contact relay (NC NO) on RX (also for TX tamper)	Free contact relay (NC NO) on RX (also for TX tamper)	Free contact relay (NC NO) on RX (also for TX tamper)
Yes with dedicated OC	Yes with dedicated OC	Yes with dedicated OC	Yes with dedicated OC
IP65	IP65	IP65	IP65
	80mm x from 1200mm to 4000mm		80mm x from 1200mm to 4000mm
60 mm x 60 mm from 500 to 4000 mm		60 mm x 60 mm from 500 to 4000 mm	