

## SELF POWERED ACTIVE INFRARED COLUMN

### CHARACTERISTICS

- Battery supplied 3,6V—19Ah
- 2 ÷ 6 dual beams 3TX & 3RX — range 50 m.
- Alignment SMA.
- Low battery alert
- Fog disqualification
- Adjustable reaction time 50 ÷ 500 mSec
- Life of batteries 36÷72 months (6 ÷ 2 double beams)
- Tamper and low battery alert of TX column transmitted optically to RX column
- Outputs : Alarm, Tamper, Fog disqualification, Low battery
- Compatible with all Wireless systems
- Only TX or only RX column available
- Output (3 o 3,6V) for wireless transmitter supply
- Operating temperature -25° ÷ +65°
- Anodized aluminium structure;
- Dimensions:  $\Phi$  8cm—h. 1,2m ÷ 3m
- Anti crawl function



### SMA OPTICS

The new SMA technology (Single Man Alignment) allows the optical alignment thanks to efficient LED visible at 200m and buzzer for indicating the best signal without using other tools. This function is activated by pressing a button on each optic.

### ACCESSORIES

#### SA/BK2

Batteries  
3,6V 19Ah



#### POB 30

Cable pit



#### LAMP 30

Globe with lamp  
support



CODE	DESCRIPTION	TYPE OF PRODUCT
PARVIS SMA WS 412	Column composed with 4 dual optical beams 2TX + 2RX H 120 cm. Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 416	Column composed with 4 dual optical beams 2TX + 2RX H 160 cm. Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 420	Column composed with 4 dual optical beams 2TX + 2RX H 200 cm. Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 620	Column composed with 6 dual optical beams 3TX + 3RX H 200 cm. Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 625	Column composed with 6 dual optical beams 3TX + 3RX H 250 cm. Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 212 R / PARVIS SMA WS 212 T	Column with 2 dual optical beams RX o TX H 120 cm. - Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 216 R / PARVIS SMA WS 216 T	Column with 2 dual optical beams RX o TX H 160 cm. - Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 220 R / PARVIS SMA WS 220 T	Column with 2 dual optical beams RX o TX H 200 cm. - Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 320 R / PARVIS SMA WS 320 T	Column with 3 dual optical beams RX o TX H 200 cm. - Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
PARVIS SMA WS 325 R / PARVIS SMA WS 325 T	Column with 3 dual optical beams RX o TX H 250 cm. - Internal Battery Kit SA/BK2. Range max 50 m.	SINGLE COLUMN
SA/BK2	Battery 3.6V 19000mAh with connectors - (2 pcs)	ACCESSORIES
POB 30	Cable pit for Parvis and Mana columns	ACCESSORIES
LAMP 30	Lamp bowl 30cm Diameter	ACCESSORIES