



WI-CPE511-KIT
5.8GHz 300Mbps
Outdoor Wireless Transmitter for CCTV
Data sheet

Highlights

- 200mW High power output, coverage up to 5km for PTP and PTMP wireless CCTV application
- 5.8G Wireless A/N speed up to 300Mbps
- 5km wireless transmit for Carry 10-20pcs 1080P camera
- Easy setup for PTP/PTMP application, no need setting software
- Support open frequency from 4920 to 6100 MHz
- Inside 60 degree 16dBi Directional Antenna Technology
- 23dBm High-Power design
- 2x2 MIMO Technology
- Passive PoE Adapter supports up to 100 meter
- 1 *100Mbps Port design
- Qualcomm AR9342 600MHz Chipset, 64MB RAM
- 10KV Lightning Protection

Tx Power Specs				Rx Power Specs			
	Data Rate	Tx Power	Tolerance		Data Rate	Sensitivity	Tolerance
802.11a	6-24 Mbps	27 dBm	±2dB	802.11a	6-24 Mbps	-94 dBm	±2dB
	36 Mbps	25 dBm	±2dB		36 Mbps	-82 dBm	±2dB
	48 Mbps	23 dBm	±2dB		48 Mbps	-79 dBm	±2dB
	54 Mbps	23 dBm	±2dB		54 Mbps	-76 dBm	±2dB
802.11n	MCS0	27 dBm	±2dB	802.11n	MCS0	-93 dBm	±2dB
	MCS1	27 dBm	±2dB		MCS1	-88 dBm	±2dB
	MCS2	27 dBm	±2dB		MCS2	-86 dBm	±2dB
	MCS3	27 dBm	±2dB		MCS3	-82 dBm	±2dB
	MCS4	26 dBm	±2dB		MCS4	-80 dBm	±2dB
	MCS5	24 dBm	±2dB		MCS5	-75 dBm	±2dB
	MCS6	23dBm	±2dB		MCS6	-73 dBm	±2dB
	MCS7	23 dBm	±2dB		MCS7	-72 dBm	±2dB
	MCS8	27 dBm	±2dB		MCS8	-93 dBm	±2dB
	MCS9	27 dBm	±2dB		MCS9	-89 dBm	±2dB
	MCS10	27 dBm	±2dB		MCS10	-87 dBm	±2dB
	MCS11	27 dBm	±2dB		MCS11	-82 dBm	±2dB
	MCS12	26 dBm	±2dB		MCS12	-81 dBm	±2dB
	MCS13	24 dBm	±2dB		MCS13	-75 dBm	±2dB
	MCS14	23 dBm	±2dB		MCS14	-73 dBm	±2dB
MCS15	23 dBm	±2dB	MCS15	-72 dBm	±2dB		

Product



Description

Wi-Tek's WI-CPE511-KIT is a 5GHz 300Mbps 2x2 MIMO outdoor wireless CPE based on 802.11a/n technology. It is high performance, cost-effective and dedicated to long distance wireless network solutions. Featuring the revolutionary Wi-Tek technology in firmware design and 16dBi directional dual-polarized antenna, WI-CPE511-KIT is specialized designed for rural Internet access, long distance wireless data transmission, wireless coverage extension and other industrial wireless solutions. is widely used in various fields of communication:

- ◆ Wireless Video Surveillance
- ◆ Enterprise wireless LAN interconnection
- ◆ Mobile operators WISP large customer access system
- ◆ Wi-Fi Wireless city coverage
- ◆ Point-to-point,Point-to-multipoint wireless communication

Typical Applications



Specifications

HARDWARE FEATURES	
Processor	Qualcomm AR9342
Memory	64MB SDRAM 8MB Flash
Interface	1X10/100BASE-TX Ethernet Interface

Power Supply	24V Passive PoE Adapter Included
Power Consumption	6W
Dimensions (H x W x D)	160x105x52mm
Antenna Type	Built-in 16dBi Dual-polarized Antenna Horizontal beam width: 60degree Vertical beam width: 15degree
Protection	10KV Lightning Protection
Enclosure	Outdoor UV Stabilized Plastic IP67 waterproof Certification

WIRELESS FEATURES	
Standard Protocol	CSMA/CA,TCP/IP,IPX/SPX, NetBEUI, DHCP
Wireless Mode	AP, Client
Wireless Speeds	11a:54M,48M,36M,24M,18M, 12M,9M,6Mbps 11n:6.5M, 13M, 13.5M, 19.5M, 26M, 27M, 39M, 40.5M, 52M, 54M, 58.5M, 65M, 81M, 108M,

WIRELESS FEATURES	
	121.5M, 135M, 150M, 270M, 300Mbps
Frequency	4920-6100MHz
Transmission Power	23dBm(200mW)

SOFTWARE FEATURES	
Wireless Configurations	802.11a/n Modes Selectable Channel Width: 20/40MHz Automatic Channel Selection Transmission Power Control Dynamic Frequency Selection (DFS) WDS Enable/Disable Security: WPA/WPA2, WPA-PSK/WPA2-PSK (AES/TKIP) Encryption, 64/128/152-bit WEP Encryption SSID Broadcast Enable/Disable Distance/ACK Timeout Setting Wireless MAC Address Filter Wireless Advanced: > Beacon Interval/RTS Threshold/Fragmentation >Threshold/DTIM Interval/AP Isolation/Short GI/Wi-Fi Multimedia
Management	WEP management

SOFTWARE FEATURES	
System-level Optimizations	Optimized IGMP Snooping/Proxy for multicast applications Hardware watch dog

OTHERS	
Certification	CE
Package Contents	2*CPE 2*PoE Adapter 2* Pole Mounting Kit included
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX or Linux. Note: We recommend you to use one of following Web browsers for an improved user experience: Google Chrome, Safari, and Firefox. IE browsers are not recommended.
Environment	Working Temp: -40 ~ 70°C Storage Temp: -40 ~85°C Working Humidity: 10%~95% non-condensing