

COLOUR VDS LOFT MEMORY MONITOR



Reference: 03299

Video door entry COLOUR monitor. TFT screen 3.5".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

DESCRIPTION

Video door entry COLOUR monitor. TFT screen 3.5".

Installed in homes, lets you communicate with the outside panel, open the door and see the visitor on the built-in screen .

A new concept in home monitors. Integrated design, in line with new trends and lifestyles, simple and functional, combining quality and design. The harmony of the gentle, relaxed shapes and the integrated volume concept are the synthesis of LOFT technology and design.

Its purity of line, technology and performance make this equipment an elegant and perfect element for any home.

Made in high impact ABS plastic, with a textured finish for easy cleaning and ultraviolet protection for greater resistance to sunlight.

VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "Door open, please close after entering".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.

TECHNICAL SPECIFICATIONS

FERMAX

With 2 pushbuttons for screen captures management

Screen TFT 3.5".

Resolution: 480 (H) x 234 (V) lines.

Terminal has a built-in magnet in the earpiece area that ensures the arm is well fitted and fixed to the base.

This prevents the arm falling off damaging the wall when hanging up and also avoids faults caused in the installation by being badly hung.

Dimensions: 220x203x60 mm (height-width-depth):

Power supply: 18 Vdc

Door release and guard unit call button.

Auto-on button for main and secondary camera activation (sequentially).

Call volume control

Colour, brightness and contrast control.

On/off control

Door bell: for direct house call button connection to monitor/telephone.

Selectable call tunes.

Video memory that automatically memorizes the images caught on camera, from the outdoor panel, when a call takes place. These images can be viewed on the monitor screen later, indicating the date and time they were taken.

Private communication. Conversation secrecy.

Weight: 0,836236 kg

Size of product when packed: 27,2x23,9x6,5 cm

EAN 13: 8424299032993
