


NGC-7251FM

5MP Network IR Water-Proof Dome Camera



- 5MP (2592 × 1944) H.265 full real time coding
- Max.resolution: 2592 × 1944; ICR auto switch, true day / night
- 20 ~ 30m IR night view distance
- 3D DNR, true WDR, HLC, BLC, Smart IR and ROI coding
- One CVBS output and one on-board CVBS output
- One MIC IN and one built-in MIC; Hardware reset
- DC12V/PoE power supply
- Support smart phone, iPad, remote monitoring
- IP67&IK10 ingress protection
- Support three streams
- P2P function optional
- Support face detection
- Smart analytics (optional): object removal detection, abnormal video signal detection, line crossing detection, region intrusion detection, people intrusion detection, people counting detection and crowd density detection




SPECIFICATIONS

Model Specifications	NGC-7251FM
Camera	
Image Sensor	1 / 2.5 "CMOS
Image Size	2592x1944
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed Iris
Min. Illumination	0.036 lux @F2.0, AGC ON; 0 lux with IR 0.013 lux @ F1.2, AGC ON; 0 lux with IR
Lens	2.8 mm @F1.85, horizontal field of view: 101° 3.6 mm @F1.6, horizontal field of view:79°
Lens Mount	M12
Wide Dynamic Range	120dB
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan : 0°~355°, Tilt : 0°~67°, Rotation : 0°~355°
Image	
Video Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	5MP (2592 × 1944), 4MP (2592 × 1520), 2K (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream	60Hz : 5MP(1~30fps)/4MP(1~30fps)/ 2K(1~30fps)/ 3MP(1~30fps)/ 1080P(1~30fps)/ 720P(1~30fps) 50Hz : 5MP(1~25fps)/ 4MP (1~25fps) / 2K (1~25fps) / 3MP (1~25fps) / 1080P (1~25fps) / 720P (1~25fps)
Sub Stream	60Hz : 720P(1~15fps)/D1(1~30fps)/CIF (1~30fps); 50Hz:720P(1~15fps)/D1(1~25fps)/CIF (1~25fps)
Third Stream	60Hz : D1/CIF/480 × 240 (1~30fps); 50Hz: D1/CIF/480 × 240 (1~25fps)
High Frame Rate Mode	Main stream: 1080P/720P(1~60fps/1~50fps)
Bit Rate	128 Kbps ~ 10 Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G711A / U
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen, NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Video Output	CVBS output (BNC × 1); on-board CVBS output × 1
Audio	MIC IN × 1; built-in MIC × 1
Storage	Built-in micro SD card slot; up to 128GB
Hardware Reset	Yes
Functions	
Remote Monitoring	Web browsing,CMS remote control
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network remote storage; micro SD cardstorage
Smart Alarm	Motion detection; SD card error; SD card full
Intelligent Analytics	Face detection (object removal detection, regional intrusion detection, abnormal video detection, line crossing detection, people intrusion, people counting, crowd density optional)
General function	Watermark, IP address filtering, video mask, heartbeat, password protection

PoE	Yes
IR Distance	20 ~ 30 m
Ingress Protection	IP67&IK10
Others	
Power Supply	DC12V/PoE
Power Consumption	< 9W
Operating Environment	- 30 °C ~ 60 °C (-22°F~140°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 119 × 87.8
Weight (net)	Approx. 0.65KG
Installation	Ceiling mounting (Wall mounting available with the junction box and bracket

DIMENSIONS



AVAILABLE ACCESSORIES

