

DUOX PLUS VEO 4.3" MONITOR

**Reference:** 9445

The VEO monitor is made of high-impact ABS plastic. Texturized finish for easy cleaning and ultraviolet protection to get more resistance to the light. VEO incorporates a 4,3" (16:9) panoramic color...

DESCRIPTION

The VEO monitor is made of high-impact ABS plastic. Texturized finish for easy cleaning and ultraviolet protection to get more resistance to the light. VEO incorporates a 4,3" (16:9) panoramic color TFT screen. Its unique handset design incorporating a magnet enables the user to put it back into position correctly when the call is finished. Its balanced design of pure lines is distinguishing, modern and minimal. VEO integrates in the ambience.

When a call is received, the image appears automatically. When the handset is picked up a conversation with the visitor can take place. The image is de-activated automatically after 90 seconds, or when the handset is put back in position. To open the door, press the button with a key.

TECHNICAL SPECIFICATIONS

GENERAL CHARACTERISTICS

Technology: DUOX PLUS (non-polarised 2 wire full digital system)

Audio/Video system: Audio/Video Color

Set-up (Installation): Surface mounted (order connector ref. 9447 separately)

Desktop support: Yes (ref. 9410)

Handset with magnet to facilitate the hang up: Yes

Induction loop available: Yes (replace handset with ref. 3443 or order monitor ref. 9455 which already includes the induction loop))

Screen dimensions: 4,3" (Panoramic 16:9)

Screen resolution (H x V): 480 x 272

Color of the product: Matt white

Number of pushbuttons: 4

Kind of pushbuttons: Mechanical (silicone)

Number of leds for lighted indications: 1 (red with 3 states: always ON, slow/fast blinking)

PROGRAMMING OF THE TERMINAL ADDRESS

From the terminal: From the OSD menu

From the outdoor panel or guard unit: Yes

From the outdoor panel throughout the apartment door bell: Yes

FEATURES

Automatic picture capture when the visitor calls (PHOTOCALLER): Yes (1 photo/call, until 150 photos, 368 x 288 pixels). This feature can be enabled by the user. Disabled by default.

Guard unit call: Yes (by means of the door release button)

Auto-on: Yes (with 3 outdoor panels/cameras)

OSD menu: Yes

Additional function F1: Yes (Button F1 sends a negative and/or command)

Additional function F2: Yes (it only sends command, no negative)

Apartment door bell differentiated from the outdoor panel: Yes

Connection for additional devices (call extension, light/buzzer activator, etc.): Yes (ref. 2040, ref. 2438, ref. 3267)

Additional terminals on the same address: Yes, max. 2 additional terminals (additional power supply can be required)

Doormatic (automatic door release for offices, etc.): No

ADJUSTMENTS

Date and time: Yes

Ring tones selection: Yes (5). Configurable for Block Panel 0, Block Panel 1, General Entrance Panel 0 and Concierge unit.

Call volume control: Yes (10 levels by OSD menu)

Do-not-disturb mode: Yes (by OSD menu) + Red led indication

Audio volume control: Yes (10 levels by OSD menu)

Brightness, color and contrast control: Yes (by OSD menu)

TECHNICAL FEATURES

Product dimensions (width x height x depth) mm: 200 x 200 x 23 (44 including handset)

Time to answer or open the door since the call is done: 30 s.

Conversation time: 90 s.

Conversation privacy: Yes

Voltage: 18-24 Vdc

Maximum consumption: 5.2 W

Standby consumption: 0.8 W

Working temperature (°C, °F), Humidity: [-5°C, +40°C][23°F, 104°F], [0%, 90%]

Line adaptor included in the terminal: Yes (A, C, default position OFF)

Connections: Bin, Bin, Bout, Bout, -, A+, F1, T

Weight: 0,5307 kg

Size of product when packed: 5,1x22,2x20,7 cm

EAN 13: 8424299094458