

INTEGRATED SECURITY SYSTEMS
BUILDING AUTOMATION

Head Office:

Via Brescia 24 G 20063 Cernusco sul Naviglio (MI) Tel. + 39 02.27.20.13.52 E-mail: info@teledata-i.com

www.teledata-i.com

EC - Declaration of performance

N.50/2019

According to Regulation EU No. 305/2011

1- Code of the product / type: **TELEDATA ONE_AP.**

2- Type number: **TELEDATA ONE_AP**.

Description: Addressable Fire Alarm Control Panel

3- Intended use or uses of the constructionproduct, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Fire detection and fire alarm systems installed in and around buildings

4- Manufacturer: **Teledata s.r.l.**, operational headquarters: **Via Brescia**, **24/G Cernusco S/N - 20063 Milano** registered office: **Via Giulietti**, **8**, **20132 Milano**, **Italy**

5- Trading Company: **Teledata s.r.l.**, operational headquarters: **Via Brescia**, **24/G Cernusco S/N - 20063 Milano** registered office: **Via Giulietti**, **8**, **20132 Milano**, **Italy**

6- System of assesment: System 1

7- Notify Body: LGAI Technological Center, S.A. (APPLUS) Campus UAB- Ronda de la Font del Carme s/n 08193 Bellaterra (Barcellona)

Notify Body Number: 0370

EC Certificate n°: 0370 - CPR - 3635





INTEGRATED SECURITY SYSTEMS BUILDING AUTOMATION

8- Declared Performance:

Essential characteristics	Performance	Harmonized technical spec. EN 54/2:1997/A1:2006:AC1999	Harmonized technical spec. EN 54/4:1997/A2:2006:2006/AC:1999
Performance under fire conditions	PASS	cl. 4,5,7	-
Response delay (response time to fire)	PASS	cl. 7.1, 7.7	-
Operational reliability	PASS	cl.4 to 10, 12,13,14	cl. 4, 5, 6, 7, 8
Performance of power supply	PASS	-	cl. 4, 5, 6
Durability of operational reliability and response delay -temperature resistance	PASS	cl. 15.4	cl. 9.5
Durability of operational reliability and response delay -vibration resistance	PASS	cl. 15.6, 15.7, 15.15	cl. 9.7, 9.8, 9.15
Durability of operational reliability and response delay -electrical stability	PASS	cl. 15.8, 15.13	cl. 9.9
Durability of operational reliability and response delay -humidity resistance	PASS	cl. 15.5, 15.14	cl. 9.6, 9.14

9- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Your Faithfully. October 24th, 2019

Luca SEBASTIO Quality Manager

Mue Solch

