

IPC-T24-L

IPC-T24-L



4MP Smart Dual Light Lite AI dome for outdoor use



- Vesta Advanced Video IP Dome
- 4MP@25/30ips, H.265
- 0.006 lux, Smart Dual Light 30m
- Fixed lens 2.8 mm
- Digital WDR, 3D-NR
- Perimeter protection and intelligent motion detection
- Built-in microphone
- SD slot, reset button
- RJ45, Onvif, IP67, PoE.



Reference / Model	IPC-T24-L / IPC-T24-L
4 megapixel 1/2.8" CMOS sensor	
H.265, H.264 video formats	
Up to 4MP resolution	
Stream 1: 4MP (1~25/30 fps)	
Stream 2: D1 (1~25/30 fps)	
Stream 3: 720P (1~25/30 fps)	
Day/Night Mode	
Smart Dual Light1 IR led (30 meters) + 1 warm light led (30 meters)	
0.006 lux, 0 lux with activated illumination	
Fixed lens 2.8 mm	
Image modes: BLC, HLC, digital WDR, 3D-NR, Mirror.	
White balance	
Automatic and manual gain control	

## 4MP Smart Dual Light Lite AI dome for outdoor use

Reference / Model	IPC-T24-L / IPC-T24-L
4-Zone video sensor and 4-Zone privacy mask	
Perimeter protection with cross-line detection and intrusion detection (supports person/vehicle classification)	
Intelligent motion detection	
Built-in microphone	
Network interface: RJ45 (10/100 Base-T)	
MicroSD card slot up to 256GB (not included)	
Reset button	
Network protocols: TCP/IP, UDP, HTTP, DHCP, DDNS, FTP, UPNP	
Onvif, CGI, P2P, SDK and API support	
Compatible with IE8 and later browsers	
Management software	
Compatible with IOS and Android mobile devices	
Power supply: 12V DC / PoE (802.3af)	
Maximum power consumption: 3W	
Storage temperature from -40°C ~ +60°C	
Operating temperature from -30°C ~ +60°C	
Operating relative humidity <95%.	
IP67 degree of protection	
Metal inner core and plastic housing	
Dimensions: Ø110 x 97 mm	
Net weight: 430 g	