

IPC-T38-L-MC-PV

IPC-T38-L-MC-PV



8MP Smart Dual Light Active Deterrence Magic Color Outdoor IP Dome



- Vesta Advanced Video IP Dome with Magic Color technology
- 8MP@20ips, H.265+
- 0.006 lux, Smart Dual Light 40m
- Fixed lens 2.8 mm
- WDR 120dB, 3D-NR
- Perimeter protection and intelligent motion detection
- Active deterrence
- Built-in microphone and speaker
- MicroSD slot, reset button
- RJ45, Onvif, IP67, PoE.



| Reference / Model | IPC-T38-L-MC-PV / IPC-T38-L-MC-PV |
|--|-----------------------------------|
| 8-megapixel 1/1.8" CMOS sensor | |
| H.265+, H.264+, H.265, H.264 video formats | |
| Resolution up to 8MP (3840x2160) | |
| Stream 1: 8MP (1~20 fps) | |
| Stream 2: D1 (1~25/30 fps) | |
| Stream 3: 720P (1~25/30 fps) | |
| Day/Night Mode | |
| Smart Dual Light: IR light 40 meters, warm light 40 meters | |
| Magic Color technology for color images in any environment | |
| 0.006 lux, 0 lux with lighting on | |
| Fixed lens 2.8 mm | |
| Image modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror | |
| White balance | |

8MP Smart Dual Light Active Deterrence Magic Color Outdoor IP Dome

| Reference / Model | IPC-T38-L-MC-PV / IPC-T38-L-MC-PV |
|---|-----------------------------------|
| Automatic and manual gain control | |
| 4-Zone video sensor and 4-Zone privacy mask | |
| Perimeter protection with cross-line detection and intrusion detection (supports person/vehicle classification) | |
| Intelligent motion detection | |
| Built-in active deterrent with audible and luminous alarm (blue and red lights) | |
| Alarm arming/disarming | |
| Built-in microphone and speaker | |
| MicroSD card slot up to 256 GB (card not included) | |
| Reset button | |
| Network interface: RJ45 (10/100 Base-T) | |
| Network protocols: TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPOE, UPNP,SMTP | |
| Onvif, CGI, P2P, SDK and API support | |
| Compatible with IE8 and later, Chrome and Firefox browsers | |
| Management software | |
| Compatible with IOS and Android mobile devices | |
| Power supply: 12V DC ($\pm 30\%$) / PoE (802.3af) | |
| Power consumption: 2.8 W (basic), 5.5 W (maximum) | |
| Storage temperature: $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$ ($-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$) | |
| Operating temperature $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$ ($-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$) | |
| Operating relative humidity <95%. | |
| IP67 degree of protection | |
| Metal housing | |
| Dimensions: $\varnothing 122 \times 110$ mm | |
| Net weight: 630 g | |