IPC-D38-AS-L

IPC-D38-AS-L

8MP Pro AI vandal-resistant outdoor IP dome

- Vesta Advanced Video IP Dome
- 8MP@25ips, H.265+
- 0.007/0.0007 lux, Smart IR 40m
- Fixed lens 2.8 mm
- WDR 120dB, 3D-NR
- Perimeter protection, face detection, people counting, heat map and intelligent motion detection
- Built-in microphone and speaker
- MicroSD slot, reset button
- RJ45, Onvif, IP67, IK10, PoE.

Reference / Model	IPC-D38-AS-L / IPC-D38-AS-L
1/2.7" 8-megapixel CMOS sensor	
H.265+, H.264+, H.265, H.264 video formats	
Resolution up to 8MP (3840x2160)	
Stream 1: 8MP (1~25 fps)	
Stream 2: D1 (1~25/30 fps)	
Stream 3: 720P (1~25/30 fps)	
Day/Night mode with removable mechanical filter	
Smart IR up to 40 meters	
0.007 lux (color), 0.0007 lux (B/W), 0 lux with luminance activated	
Fixed lens 2.8 mm	
Angle of view: 107°(H), 56°(V), 127°(D)	
Imaging modes: BLC, HLC, WDR 120dB, 3D-NR, Mirror.	
White balance	

IPC-D38-AS-L

IPC-D38-AS-L

8MP Pro AI vandal-resistant outdoor IP dome

Reference / Model	IPC-D38-AS-L / IPC-D38-AS-L
Automatic and manual gain control	
4-Zone video sensor and 4-Zone privacy mask	
Perimeter protection with cross-line detection and intrusion detection (supports person/vehicle classification)	
Face detection	
People counting	
Heat map	
Intelligent motion detection	
Built-in microphone and speaker	
Reset button	
MicroSD card slot up to 256 GB (card not included)	
Network interface: RJ45 (10/100 Base-T)	
Network protocols: TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPOE, UPNP, SMTP	
Onvif, CGI, P2P, SDK and API support	
Up to 20 users	
Compatible with IE8 and later, Chrome and Firefox browsers	
Management software	
Compatible with IOS and Android mobile devices	
Power supply: 12V DC / PoE (802.3af)	
Power consumption: 2.5W (basic), 5.2W (maximum)	
Storage temperature from -40°C ~ +60°C	
Operating temperature -30°C ~ +60°C (-30°C ~ +60°C)	
Operating relative humidity <95%.	
IP67 degree of protection	
Vandal protection IK10	
Metal housing	
Dimensions: Ø122 x 102 mm	

IPC-D38-AS-L

IPC-D38-AS-L

8MP Pro AI vandal-resistant outdoor IP dome

Reference / Model	IPC-D38-AS-L / IPC-D38-AS-L
Net weight: 490 g	