

4MP IP PTZ dome Smart Dual Light Active Deterrence Lite AI outdoor PTZ dome



- Dome PTZ IP Vesta Advanced Video
- 4MP@25/30ips, H.265
- ICR, 0.007/0.0004 lux, Smart Dual Light 120m
- 25X optical zoom (5.5~137.5mm)
- 3D-DNR, ROI
- Pan&Tilt: 360°@120°/s (H); 90°@120°/s (V); 250 presets
- 1 audio input / 1 audio output
- 1 alarm input / 1 alarm output
- MicroSD slot, reset button, RJ45, Onvif, IP66
- 12V DC / PoE+



Reference / Model	SD4Z25-AS-PV / SD4Z25-AS-PV
4 megapixel 1/2.8" CMOS sensor	
H.265, H.264 and MPEG video formats	
Resolution: 4MP (2560x1440), 1080P (1920x1080), 1.3MP (1280x960), 720P (1270x720), D1 (704x576)	
Stream 1: 4MP, 1080P, 1.3MP, 720P (1~25/30 fps)	
Stream 2: D1 (1~25/30 fps)	
Day/Night mode with removable mechanical filter	
Smart Dual Light120 meters	
0.001 lux F1.5 (color), 0.0005 lux F1.5 (B/W)	
Optical zoom 25X: 5.5 ~ 137.5 mm	
Angle of view: 53.6° ~ 3.08° (H)	
16X digital zoom	
Imaging modes: BLC, EIS, 3D-NR, Defog	
Supports ROI of a fixed region for each stream	

4MP IP PTZ dome Smart Dual Light Active Deterrence Lite AI outdoor PTZ dome

Reference / Model	SD4Z25-AS-PV / SD4Z25-AS-PV
Horizontal positioner: 0° ~ 360° continuous	
Vertical positioner: -18° ~ 90°	
Speed: 0.1° ~ 120°/sec (H), 0.1° ~ 120°/sec (V)	
255 presets	
6 rounds (up to 18 presets per round)	
4 patterns with a total recording time of not less than 10 min.	
Built-in active deterrent with audible and luminous alarm (blue and red lights)	
Alarm arming/disarming	
1 audio input / 1 audio output	
1 alarm input / 1 alarm output	
MicroSD card slot up to 256 GB (card not included)	
Reset button	
Network interface: RJ45 (10/100 Base-T)	
Network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, RTP, RTSP, RTCP, NTP, SMTP, SNMP, IPv6	
Onvif (S/G) compliant	
Power supply: 12V DC, 3 A / PoE+ (802.3at)	
Operating temperature from -40°C ~ +60°C	
Operating relative humidity <90%.	
IP66 degree of protection	
Lightning-proof 4kV	
Wall or ceiling installation	
Dimensions: Ø160 x 270 mm	
Weight: 3,5 kg	