

Entry Series 6-channel IP NVR with 4 PoE



- NVR IP Vesta Advanced Video Entry Series 6-channel
- H.265/H.264
- 88/88 Mbps input/output
- Simultaneous HDMI (4K) and VGA (1080P) outputs
- AI from cameras: Perimeter protection, face detection, people counting and SMD
- 1 SATA HDD capacity
- 1 RJ45 Fast Ethernet
- 2 USB 2.0
- 12V DC, 4 PoE



Reference / Model	NVR2106M-4P / NVR2106M-4P
6 IP channels	
Video compression: H.265 and H.264	
Simultaneous video outputs HDMI (4K) and VGA (1080P)	
Output division: 1, 4, 9	
1 input / 1 output RCA audio	
Bi-directional audio	
Audio compression: G.711a	
Recording resolution up to 8MP (3840x2160)	
Bandwidth: 88 Mbps in, 88 Mbps out	
Decoding capacity:	
1 channel at 8MP (30 fps)	
4 channels 1080P (30 fps)	
Supports adaptive decoding	

Entry Series 6-channel IP NVR with 4 PoE

Reference / Model	NVR2106M-4P / NVR2106M-4P
Manual, scheduled recording modes (general, videosensor, alarm, intelligence)	
Alarm link: Recording, Snapshot, Buzzer, Log, Preset, Email	
Supports image capture in JPEG format	
Artificial Intelligence from intelligent cameras:	
Perimeter protection (intrusion, line crossing).	
Face detection	
People counting	
Intelligent motion detection	
Artificial Intelligence in the recorder:	
Not available	
AI search by target classification (people, motorized vehicles and non-motorized vehicles)	
Synchronized playback of up to 6 channels	
Internal capacity for 1 SATA HDD up to 14TB (sold separately)	
4 PoE (802.3af) 10/100Mbps ports	
RJ45 Fast Ethernet network port (10/100Mbps)	
Network protocols: HTTP, TCP/IP, IPv4, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, Auto register	
Onvif and SDK support	
Compatible with IE8 or later web browser	
Compatible with Android and iOS devices	
Communication ports: 2 USB 2.0 ports	
Power supply: 12V DC, 2A	
Power consumption: 7 W (excluding hard disk)	
Operating temperature from -10°C ~ +55°C	
Relative humidity 10%~90% (non-condensing)	
Metal housing	

NVR2106M-4P

NVR2106M-4P



Entry Series 6-channel IP NVR with 4 PoE

Reference / Model	NVR2106M-4P / NVR2106M-4P
Dimensions: 255 (W) x 42 (H) x 222 mm (Mini 1U)	
Weight: 900 g	
Desktop installation	
CE/FCC certified	