

PIR and glass break detector



- PIR and glass break detector
- PIR range up to 12 meters, 90°
- Microphonic range up to 8 meters
- Anti-pet up to 25 kg
- Remote adjustable anti-pet sensitivity and immunity levels
- EN50131 Grade 2 certified



Reference / Model	VESTA-382 / IRAGS-35SL-F1-2W-868
Dual technology multi-function PIR and glass breakage detector	
Combines a PIR motion detector with an acoustic glass break detector.	
Its unique dual functionality is capable of detecting motion in a designated room and determining glass breakage.	
Inheriting the advantages of its predecessor IR-35, IRAGS-35 offers remote control of sensitivity level and pet immunity settings	
PIR range of up to 12 meters, 90°.	
Microphonic range up to 8 meters (adjustable sensitivity: 8/5/3/1.5 meters)	
Features a special lens made with advanced technology to help reduce blind spots	
Immunity for pets up to 25 kg	
Equipped with microphonic technology to recognize acoustic patterns and provide full glass breakage detection coverage	
Alerts home and business owners when a window or glass door is being shattered or broken while monitoring the condition of the glass	
868 MHz radio frequency	

PIR and glass break detector

Reference / Model	VESTA-382 / IRAGS-35SL-F1-2W-868
Periodic supervisory signals to check system integrity	
Temperature compensated sensitivity control	
Flexible installation height from 2.3 to 2.5 meters (8 to 8.5 feet)	
Powered by 3 CR123 lithium batteries	
Battery life of 5 years	
Operating temperature -10°C ~ +45°C (-10°C ~ +45°C)	
Relative humidity up to 85% (non-condensing)	
Dimensions: 69 (W) x 112 (H) x 37 mm	
EN50131 Grade 2 certified	