

Outdoor PIRCAM detector













- VESTA SF1 PIRCAM radio detector for outdoor use
- Product developed in collaboration between Optex and Vesta
- Two independent IR lenses
- Adjustable range from 2.5 to 12 meters
- Anti-masking
- Anti-pets up to 25 kg
- Walk test
- Transfer of files and HD images at high speed (SF1)
- Swivel angle up to 90°
- Installation height of $0.8 \sim 1.2$ meters
- IP55 protection
- Grade 2



Reference / Model	VESTA-370 / VST-894-IL
PIRCAM VESTA detector for outdoor use	
Product developed thanks to the collaboration between Optex and Vesta.	
Incorporates SF1, the fastest radio transmitter on the market	
Adjustable detection range: 2.5 ~ 12 meters (5 levels), 90°.	
90° rotatable angle (left 45°, right 45°)	
16 detection zones	
Active IR anti-masking	
Anti-pet up to 25 kg	
Remote adjustment of pet immunity, sensitivity and temperature setting	
Temperature compensation and environmental noise immunity	
Camera with HD CMOS and 102° viewing angle	
Resolution: 720P (1280x720), VGA (640x480), QVGA (320x240)	
Four alarm image processing options: 1280x720@3ips, 640x480@3ips, 320x240@	03ips and <u>320x240@6ips</u>



Outdoor PIRCAM detector

Reference / Model	VESTA-370 / VST-894-IL
IR illumination up to 10 meters	
Video delivery in 30 seconds maximum (6 images for video verification alarm e	event)
Image delivery on demand	
Technological analysis enhances immunity to various noise factors, such as we oscillations	eather changes and vegetation
Tamper protection	
RF frequency: SF1 868MHz	
Double conductive shielding (blocks visible light and RFI disturbances)	
Periodic monitoring signals to ensure proper operation	
Power supply: 4 AA lithium batteries L91	
Battery life up to 9 years	
Operating temperature -20°C ~ +55°C (-20°C ~ +55°C)	
Relative humidity up to 95% (non-condensing)	
IP55 degree of protection	
Wall/corner mounting	
Dimensions: 98.5 (W) x 276.9 (H) x 115 mm	
EN50131 Grade 2, Class IV certified	