

PIR Detector V-MAX BUS for VESTA



- PIR detector V-MAX BUS for VESTA
- Coverage 15 meters, 130°
- Anti-pets 45 kg (remote configurable)
- Automatic calibration of the PIR sensor
- Double detection function configurable from Installer App
- 2 levels of sensitivity (configurable remotely)
- Efficient rest time between detections
- Optional swivel bracket
- BUS power supply
- EN50131 Grade 2 Certificate



Reference / Model	VESTA-358 / IR-35-BUS
Detection range: 15 metres, 130°.	
Automatic PIR sensor calibration	
Dual detection function available (alarm is acknowledged in case of two detections within a short time), configurable from Installer App	
Efficient sleep time between detections	
Communication via V-MAX BUS	
Microprocessor controlled with advanced ADSP algorithms for false alarm immunity	
Anti-pets up to 45 kg	
Two selectable sensitivity levels	
Remote configurable sensor sensitivity and anti-pet function	
High false alarm immunity	
Tamper protection against tampering	
Superior white light and noise rejection	

PIR Detector V-MAX BUS for VESTA

Reference / Model	VESTA-358 / IR-35-BUS
Automatic power saving mechanism	
V-MAX BUS supervisory signals	
Radio interference rejection	
Sensitivity control with temperature compensation	
BUS power supply	
Operating temperature range -10°C ~ +45°C	
Relative humidity up to 85% (non-condensing)	
Installation height 2.3 ~ 2.5 metres	
Dimensions: 69 (W) x 104 (H) x 37 mm	
Optional swivel bracket	
EN50131 Grade 2 Certificate	