

Item		Description		
Products	Products	24 Ports Ethernet Switch	24 Ports PoE Ethernet Switch	16 Ports PoE Ethernet Switch
Power	Power Supply	Mains on load		
	Voltage Range	AC 100~240V		
	Consumption	30W	420W	320W
Network Connector	Ethernet Port	1 ~ 16/24 Ports: 10/100Mbps Ethernet port, adaptive control UPLINK Ethernet ports: 10/100/1000Mbps Ethernet port SFP: SFP optical fiber module, 1000Mbps		
	Transmission Distance	1 ~ 16/24 ports: Recommended 120m Max.150m; Uplink 1000Mbps Ethernet port: Max.150m SFP: depend on the optical module performance		
	PoE Protocol	N/A	IEEE802. 3af, IEEE802. 3at	
	PoE Power Supply	N/A	End-span	
	PoE Power Consumption	N/A	Each Port≤30W, Total≤370W	EachPort≤30W, Total ≤250W
Network Switch	Network Standard	IEEE802. 3 10BASE-T, IEEE802. 3u 100BASE-TX, IEEE802. 3ab 1000BASE-T, IEEE802. 3z 1000BASE-SX/LX		
	Switch Capacity	16G		
Management	Management	Management L2		
Protection	ESD	Level 3, Per: IEC61000-4-2		
	Communication Port Lighting Protection	Level 3, Per: IEC61000-4-5		
Environmental	Working Temperature	0℃ ~55℃		
	Storage Temperature	-40℃ ~85℃		
	Humidity (non-condensing)	0~95%		
Mechanical	Dimension (L×W×H)	442mm×263mm×44.5mm		
	Material	Sheet metal		
	Color	Black		
	Weight	3.05kg	3.73kg	3.54kg