

NGC-7216

Model	2 Megapixel IR Water-proof Dome Network Camera	
Camera	Image Sensor	1/3"CMOS
	Image Size	1920 x 1080
	Electronic Shutter	1/25s~1/100000s
	Auto Iris	Fixed Iris
	Min. Illumination	0 Lux (IR ON)
	Lens	3.6mm (2.8mm, 6mm optional)
	Day-Night Switch	ICR auto switch
	WDR	Digital WDR
	DNR	3D noise reduction
Image	Video Compression	H.264/MJPEG
	H.264 Compression	Baseline Profile/Main Profile
	Encode Mode	VBR/CBR
	Image Quality	Five levels VBR; Freely adjustable under CBR
	Bitrate	64Kbps~8Mbps
	Resolution	1080P(1920 x 1080), 720P(1280 x 720), D1, CIF, 480 x240
	Multi-streams	1920 x 1080 (1~30fps) /1280 x 720 (1~30fps) 1280 x 720 (1~10fps) /D1 (1~30fps) /CIF (1~30fps) CIF (1~30fps) /480 x240 (1~30fps)
	Image Settings	Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR., etc., adjustable through client software or web browser
Interface	ROI	Support 8 ROI areas
	Network	RJ45
Function	Remote Monitoring	IE browsing, CMS remote control
	Online Connection	Support simultaneous monitoring for up to 4 users; Support multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	Interface Protocol	ONVIF, GB-T/28181-2011
	Storage	Network remote storage
	Smart Alarm	Motion Alarm
	PoE Power Supply	Optional
	IR Distance	No(10-20 m optional)
	Water-proof	IP66
Others	Power Supply	DC12V/POE
	Power Consumption	< 2.5W (ICR OFF); < 4.5W (ICR ON)
	Working Environment	-40℃~50℃, 10%~90% humidity
	Dimension	Φ 64mm ×183mm
	Weight (Net)	599g