

## BARIERE INFRA QUAD FRECVENTE MULTIPLE

<b>Specificatii</b>				
<b>Model</b>	<b>Quad-50CS</b>	<b>Quad-100CS</b>	<b>Quad-150CS</b>	<b>Quad-200CS</b>
Distanta maxima (exterior)	50m	100m	150m	200m
Distanta maxima (interior)	100m	200m	300m	400m
Curent consumat (Tx+Rx)	110mA	115mA	120mA	125mA
Curent consumat cu heater-ul cuplat	260mA	270mA	280mA	290mA
Tensiune alimentare	AC/DC 12~24V (fara polaritate)			
Timp raspuns	50msec ~ 700msec			
Iesire de alarma	Contact releu: NC / NO. 1A / 120VAC			
Iesire tamper (Tx&Rx)	Contact NC , 1A@120VAC			
LED indicator aliniere (Rx)	LED galben – stins: aliniere corecta. LED galben - aprins: Spot intrerupt sau aliniere			
LED indicator alimentare(Rx & Tx)	LED verde aprins: Indica prezenta tensiune			
Lungime de unda LASER	650nm			
Putere LASER	<5mW			
Grad de protectie	IP-55			
Unghi aliniere	Horizontal:±90° , Vertical:±15°			
Temperatura functionare	-25°C ~ + 55°C			
Masa	2.6 kg			
Materialul carcasei	Rasina Policarbonat			
Umiditate	<70%			
Dimensiuni	387(H)×113(l)×110(L) mm			